

MEMORANDUM

DATE: April 25, 2017

TO: Board of County Commissioners

FROM: Tom Rains, County Engineer

SUBJECT: Utility permit for Green Country Sewer Company LLC

We present for your approval a utility permit for Green Country Sewer Company LLC to parallel 193rd E Avenue approximately one fourth mile north from 41st St S. Installation will be an open trench with a 10" line.

TR:bd Attachments

Original:	Michael Willis, County Clerk, for the May 1, 2017 Agenda
XC:	Commissioner John M. Smaligo, Jr. Commissioner Karen Keith Commissioner Ron Peters John Fothergill, Chief Deputy Vicki Adams, Chief Deputy Eddy Barclay, District One File

TULSA COUNTY BOARD OF COUNTY COMMISSIONERS

UTILITY PERMIT

	NO
TYPE OF INSTALLATION:	
This authority executed in the original and three copies this day of	, 20,
by the Tulsa County Board of Commissioners, hereinafter called the "COUNTY", witnesset	h:
That the COUNTY does by these presents, grant to:	
Appliant Green Country Sewerlo, L.	L-C
Mailing Address 20108 E 33 MPL So	
City Broken Arrow Zip 740	<u>,14</u>
a permit to erect, construct and maintain a Sanitory Source Force Me	along, upon or across the
hereinafter described County Highway (s) for the purpose of transporting, selling, and using	
being shown on the attached drawing (s) and further described as follows:	
To <u>Parallel</u> 193 rd <u>E. Avenue</u> cross or parallel <u>County Highway name or number</u>	approximately
miles $\frac{N}{N.E.S.W.}$ of the $\frac{H1^{5+} 5+.557L}{Junction or other definite point}$ and further described as $\frac{132}{32}$	get feet of the
5ω corner of Section <u>19</u> , Township <u>19</u>	, Range, 15E, Tulsa County.
The installation will be made in the following manner: <u>Open French</u> (boring, pushing, cut slab, over	,
Size of Line: Size of Casing:	
Exhibit A is a part of this permit.	

This permit is granted subject to the following conditions, requirements and covenants, to-wit:

- 1. Work to be performed on County right-of-way must be under the direction of the Tulsa County Engineer, who must be notified of the time when the work is to begin. Under no circumstances will any work be done on County right-of-way until approval of the Tulsa County Engineer has been obtained.
- 2. <u>One copy of an approved permit must be kept at the work site for inspection by the Tulsa County Engineer or his repre-</u> sentative. Applicant will be required to have an inspector or engineer present at all times during construction to insure that installation is made in accordance with plans.
- 3. The applicant must agree to hold the COUNTY harmless for any damage(s) or injury(ies) to any person(s) or property(ies) caused by or resulting directly or indirectly from the construction, maintenance, operation or repair of the facilities on, under, or over the County right-of-way and must further agree to reimburse the COUNTY for any repair of any damage to COUN-TY facilities caused by the construction and/or operation of the applicant's facility.
- 4. All work on the County right-of-way is to be done in accordance with the current Standard Specifications for Highway Construction, Oklahoma State Highway Commission, and at the conclusion of such work the right-of-way must be cleaned up and left in a presentable condition. This will include replacing any protective grass cover destroyed by trenching or operation of equipment, and correcting any other damage that may have been caused, as directed by the COUNTY. The applicant shall require the contractor or whoever installs the facilities to deposit with the COUNTY a cashier's check, certified check, cash or bond which is to insure the cost to the COUNTY for restoring the area to its original state, if not restored by the installer. The minimum deposit or bond will be based on fifty cents per lineal foot paralleling the highway, two dollars per lineal foot for boring and five dollars per lineal foot for trenching when trenching is necessary. The measurement to determine the amount of deposit shall be measured along centerline of trench for paralleling roadway, and for boring or trenching the measured centerline of trench from right-of-way line to right-of-way line. After final inspection by the County Engineer's Office, and an additional period of ninety days, the deposit less any amount not used to restore the area shall be returned to the depositor.
- 5. <u>The applicant must furnish all flagmen, lights, barricades, and warning signs deemed necessary by the COUNTY, during the construction maintenance, or repair of its facilities on the County right-of-way.</u>
- 6. When notified to do so by the COUNTY, the applicant agrees to make all changes in the facilities on a County right-of-way at the applicant's own expense, unless otherwise provided by law or order of the COUNTY.
- 7. Clearance above the traffic lanes of the highway at all pole line crossings should comply with applicable safety codes, but will not be less than 20 feet at a temperature of 60 degrees Fahrenheit. All poles, posts, stubs, fixtures, down guys, wires, and other appurtenances must be kept in good repair at all times and must be free from weeds and brush withing a 5-foot area no more than 4 fee inside the right-of-way line, unless otherwise approved by the COUNTY.
- 8. All underground crossings of the right-of-way must be encased from right-of-way line to right-of-way line at a minimum depth of 48 inches below the bottom of the surfacing, but not less than 30 inches below the bottom of the ditches, unless otherwise approved by the COUNTY.

All encased crossings must be sealed at both ends and vented outside of right-of-way line. The vents should be sized to allow proper release of carrier pipe contents in case of failure. The minimum pipe size for vents is 2-inch nominal, and the vent must extend a minimum of 36 inches above natural ground level. The owner must install identification markers at each right-of-way line directly above the facility. Such markers may be attached to vents or to a right-of-way fence. The markers may be in the owner's standard design, but must identify the owner and size of the facility, and must be erected at a location plainly visible from within the highway right-ofway.

The casing must be designed to sustain roadway loadings, contain and divert from the roadway the contents of the carrier pipe, and to have a life expectancy equal to or greater than the carrier pipe.

Encasement for underground telephone and power lines, or similar facilities, should comply with the above except for the installation of vents, end seals, and the ability to contain and divert.

Steel pipelines crossing the right-of-way may be installed without encasement if the installation is in accordance with "Special Provisions for the Installation of Underground Pipelines...". This Special Provision stipulates in part that carrier pipe material within the right-of-way must be superior to the carrier pipe material outside the right-of-way by being of steel at least one grade better, or a minimum of one wall width thicker and of the same alloy. Pipe must be 48 inches below the flow line of drainage ditches and all other highway drainage facilities, and must be properly protected from corrosion.

Nonpressurized facilities, such as sanitary sewer lines, crossing the highway right-of-way may be approved without the use of encasement, if cast iron or material of equal or better quality is used, with the understanding that maintenance will be performed by a method that will not disturb the through lanes or interfere with traffic.

All underground crossings must be installed by boring or pushing or other approved methods. The method and equipment for the installation must be approved by the COUNTY. Wet boring or jetting will not be permitted unless special approval is obtained from the COUNTY. If considered necessary, pressure grouting of the voids will be required. This will generally be required when the diameter of the bore exceeds the outside diameter of the pipe by two inches or more. In the interest of safety, trenching and the parking of equipment should be performed as far as possible from traffic lanes. In unusual cases where trenching is necessary, a special plan with specifications will be developed by the owner with assistance from the COUNTY, setting out the method for controlling the traffic, placement of the facility, and proper restoration of the roadway. This method must bear the recommendation of the COUNTY.

Parallel facilities must be installed no more than 4 feet inside the right-of-way line and buried a minimum depth of 30 inches below the ditch flow line. The ditch must be backfilled to a density equal to the adjacent soil, and approved by the COUNTY.

- 9. The applicant must agree to refrain from disturbing trees, shrubbery or any part of the landscape without approval of the COUNTY. If it becomes necessary to disturb trees or shrubbery, applicant intentions must be plainly stated in the application, which will include size and kind of trees and shrubs, and disposition during installation.
- 10. Blasting will not be permitted within the highway right-of-way except in unusual cases and only with special approval from the County Engineer.
- 11. The applicant must agree to hold the COUNTY harmless for any and all damage that the utility facilities might sustain while occupying County right-of-way.
- 12. Applicant assures that all necessary permits have been received from those governmental agencies from which approval is required by Federal or State law, including Section 404 of the Federal Water Pollution Control Act Amendments of 1972, 33 V.S.C. 1334.

13. Contractor for this project Cross Be Construction, address Clevemore OK 74017. This permit may be revoked for noncompliance. Accepted this _____ day of ____ Green Lountry ser l thorized Representative of Company Manager Title Attest: Secretary Accepted this _____ day of _ , 20 BOARD OF COUNTY COMMISSIONERS TULSA COUNTY, OKLAHOMA Chairman

Attest:

Form 449 (Rev. 11-99) Back